

## PRODUCT DESCRIPTION

- Basic cover dedicated to all standard Kluś extrusions
- Good light diffusion
- Meets general technical requirements
- For indoor use
- Maximum working temperature 65°C
- Maximum LED power up to 7W/m

Fill empty fields




Product nr.	
Fixture type	
Company	
Job name	
Date	


## TECHNICAL SPECIFICATION

Material	PVC
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	no


## TECHNICAL DRAWING




**RELATED PROFILES**




OPK-4 Profile  
Ref: C0370




MICRO-H Profile  
Ref: C0599




PDS-H Profile  
Ref: B9204




45-16 Profile  
Ref: B8504




OLEK Profile  
Ref: B8505




MICRO-ALU Profile  
Ref: B1888




MICRO-K Profile  
Ref: B3775




PDS-4-ALU Profile  
Ref: B1718




PDS-4-K Profile  
Ref: B3776




PDS-ZM Profile  
Ref: B7696




POR Profile  
Ref: B6144




PDS-O Profile  
Ref: B3777




45-ALU Profile  
Ref: B4023




GLAD-45 Profile  
Ref: B7009




KUBIK-45 Profile  
Ref: B7697




KOZMA Profile  
Ref: 18040




DES Profile  
Ref: 18030




POLI Profile  
Ref: B7176




NISA-PLA Profile  
Ref: 18028




NISA-KON Profile  
Ref: 18027




NISA-KRA Profile  
Ref: 18026




NISA-NI Profile  
Ref: 18029



STEP Profile  
Ref: 18042




PULA Profile  
Ref: 18035




OBIT Profile  
Ref: W4826



LIT-L Profile  
Ref: 18033




PDS-4-PLUS  
Profile  
Ref: C1263




PDS-ZMG Profile  
Ref: C1418




MICRO-HG Profile  
Ref: C1419



MOD-50 Profile  
Ref: 18047



MICRO-NK Profile  
Ref: C1587



MOD-100 Profile  
Ref: 18049