

The cover has a matt black surface that turns white when the light is turned on, line of light at 120LED/m (9.6W/m) in profiles with minimal deep 19 mm. The cover is made of UV-resistant PMMA. When the LEDs are off, it is black. The best visual effect is obtained in profiles that are black inside.

- They blend in with dark lighting fixtures and dark surfaces of ceilings or walls
- A surprising light effect when the light is switched on

Fill empty fields

Product nr.	
Fixture type	
Company	
Job name	
Date	



TECHNICAL SPECIFICATION

Application


Decorative lighting.

Assembly

Snap-in in dedicated profiles.

Material	PMMA
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	yes

TECHNICAL DRAWING






RELATED PROFILES




GIZA-LL profile Ref: C0758



KOZUS-CR Profile Ref: C0600



GIZA Profile Ref: B5556



LIPOD Profile Ref: B5554



LOKOM Profile Ref: B5553



LARKO Profile Ref: B5552




LESTO Profile Ref: B5551



OPAC-30 Profile Ref: B6164



LOC-30 Profile Ref: 18015



KOZEL Profile Ref: B6454



KOZUS Profile Ref: B7823



KIDES-DUO Profile Ref: 18032



STEPUS Profile Ref: 18038




WERKIN Profile Ref: 18025



RELATED PRODUCTS

MARKETING MATERIALS





Display P230-90154M Ref: 90154M

Foam 70271 Ref: 70271