

PRODUCT DESCRIPTION

- Flexible cover with increased UV resistance
- Snapped-in

Fill empty fields


Product nr.	
Fixture type	
Company	
Job name	
Date	



TECHNICAL SPECIFICATION

Material	PC
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	increased

TECHNICAL DRAWING





RELATED PROFILES



OPK-4 Profile Ref: C0370



MICRO-H Profile Ref: C0599



PDS-H Profile Ref: B9204



45-16 Profile Ref: B8504



OLEK Profile Ref: B8505



MICRO-ALU Profile MICRO-K Profile Ref: B1888



Ref: B3775



PDS-4-ALU Profile Ref: B1718



PDS-4-K Profile Ref: B3776



PDS-ZM Profile Ref: B7696



POR Profile Ref: B6144



PDS-O Profile Ref: B3777



45-ALU Profile Ref: B4023



GLAD-45 Profile Ref: B7009




KUBIK-45 Profile Ref: B7697



KOZMA Profile Ref: 18040



DES Profile Ref: 18030



POLI Profile Ref: B7176




NISA-PLA Profile Ref: 18028



NISA-KON Profile Ref: 18027



NISA-KRA Profile Ref: 18026



NISA-NI Profile Ref: 18029



STEP Profile Ref: 18042



PULA Profile Ref: 18035





OBIT Profile Ref: W4826



LIT-L Profile Ref: 18033



PDS-4-PLUS Profile Ref: C1263



PDS-ZMG Profile Ref: C1418



MICRO-HG Profile Ref: C1419



MOD-50 Profile Ref: 18047



MICRO-NK Profile Ref: C1587



MOD-100 Profile Ref: 18049



RELATED PRODUCTS

END CAPS



ONISA grey End cap Ref: 24100