

PRODUCT DESCRIPTION

- Well stabilized profile connections
- Possibility of building lighting fixtures with polygonal shapes

Fill empty fields

Product nr.	
Fixture type	
Company	
Job name	
Date	



TECHNICAL SPECIFICATION

Application

FOR JOINING NON-ANODIZED PROFILES, equipped with a ZM socket at 45, 60, 90, 120, 135, 180 degrees. They also give the possibility of creating T-, X-, Y-shaped fixtures from profiles equipped with 3 ZM sockets.

Assembly

With pressure screws.



RELATED PROFILES



TPK-4 Profile Ref: 18044



KOZUS-CR Profile Ref: C0600




TEKNIK-ZM Profile Ref: C0399



FOLED Profile Ref: B8332V1



FOLED-BOK profile . Ref: B8334V1



FOLED-SUF Profile KOZMA Profile Ref: B8333V1



Ref: 18040



KOZEL Profile Ref: B6454




KOZUS Profile Ref: B7823



NISA-PLA Profile Ref: 18028




NISA-KON Profile Ref: 18027



NISA-KRA Profile Ref: 18026




NISA-NI Profile Ref: 18029



KOZEL-50 Profile Ref: C0757



KOZUS-50 Profile Ref: C0958



KOZEL-10 Profile Ref: C1575



TEKNIK-ZM-TK Profile Ref: C1554



RAM-KOZE-50 Profile Ref: 18055



RAM-KOZE-100 Profile Ref: 18057



RAM-3035-KOZE Profile Ref: 18056