

PRODUCT DESCRIPTION

- Well stabilized profile connections
- Possibility of building lighting fixtures with polygonal shapes

Fill empty fields

Product nr.	
Fixture type	
Company	
Job name	
Date	



TECHNICAL SPECIFICATION

Application

FOR JOINING ANODIZED PROFILES, equipped with a ZM socket at 45, 60, 90, 120, 135, 180 degrees. They also give the possibility of creating T-, X-, Y-shaped fixtures from profiles equipped with 3 ZM sockets.

Assembly

With pressure screws.



RELATED PROFILES



GIZA-LL profile Ref: C0758



OPK-4 Profile Ref: C0370



3035 Profile Ref: 18039



JAZ Profile Ref: B8547



OLEK Profile Ref: B8505



KOPRO-30 Profile Ref: B7890



PDS-ZM Profile Ref: B7696




GLAD-45 Profile Ref: B7009




KUBIK-45 Profile Ref: B7697



GIZA Profile Ref: B5556



LIPOD Profile Ref: B5554



LOKOM Profile Ref: B5553




LARKO Profile Ref: B5552



OPAC-30 Profile Ref: B6164



KOPRO Profile Ref: B6367



DES Profile Ref: 18030




GLADES Profile Ref: 18036




KIDES-DUO Profile Ref: 18032




KIDES Profile Ref: 18031



SEPOD Profile Ref: B6593




SEKOMA Profile Ref: B6595



SEKODU Profile Ref: B6597



3035-O Profile Ref: B8441



LARKO-50 Profile Ref: C0756









PDS-ZMG Profile Ref: C1418



RAM-KOL-50 Profile Ref: 18060



RAM-KOL-100 Profile Ref: 18062